



Product Bulletin



ALUMINUM & MAG POLISH

Product Description:


Removes oxidation, rust, corrosion, stains, tarnish and water spots. Restores the original brilliance and luster to forged, machined, polished, rough cast, painted and clear coated aluminum & magnesium wheels. Also great for chrome, stainless steel, gold, silver, brass, bronze and copper surfaces. Can also be used on boats and marine hardware, RV's, engine accessories, running boards, cycle parts, trailers and more. Cleans, polishes and protects in one step. Apply by hand or machine. CONTAINS NO ACID OR WAX. VOC COMPLIANT.

Product Details:

- VOC Compliant
- NPE Free
- Phosphate Free
- pH: 8.8
- Color: White
- Fragrance: Floral

Packaging:

Quart: C-50-Q



Features & Benefits:

Removes Oxidation, Rust, Corrosion, Stains, Tarnish, Water Spots & More
Restores Original Brilliance to Forged, Machined, Polished, Painted & Clear Coated Aluminum & Mag Wheels

Application: *Shake well before using. Read label before use. See SDS for more information.*

Hand Use: Apply product to a clean microfiber wax applicator and spread evenly over surface, rubbing well in a back and forth motion, with the grain of the metal. On non-coated aluminum wheels, a black residue will appear on cloth. This is normal. On chrome, clear coated & painted aluminum surfaces, no residue will appear. Let dry to a haze (about 1 min.) and wipe off with a clean, microfiber towel. Polish by hand to a high gloss, turning towel while wiping down. Reapply as needed.

D/A Polisher: Use a PRO® YU-7-C Yellow Polish Pad. Apply product to pad. Set D/A polisher speed to 4-5. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants.

High Speed Buffer: Use a VC-80-C Wool Buffing Pad or VF-85-C Yellow Foam Compound Pad. Apply product to pad and spread evenly over small area of metal surface before buffing. Buff with adequate pressure at 1500-2300 rpm. As product disappears, reduce pressure and polish to a high gloss finish. Clean pad often to remove contaminants.

Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not apply in direct sunlight or onto a hot surface. Not for use on automotive paint finishes. Clean wheels first using PRO® C-42 Wheelie Clean™ to remove loose dirt and contaminants. Consult wheel manufacturer for care of delicate, specialty aftermarket wheels before using this product as scratching may occur.

Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com

